



Grout & Stone Sealer

For use on:

- Grout & Natural Stone
- Porous Tile
- Floors & Walls

Oil, Stain & Water Resistant

Read cautions and directions on label before use

Lea con cuidado y siga las instrucciones en la etiqueta antes de usarse

DANGER!

EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. USE ONLY WITH ADEQUATE VENTILATION. CONTENTS UNDER PRESSURE – MAY EXPLODE IF HEATED. MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION.

KEEP OUT OF THE REACH OF CHILDREN

PELIGRO!

EXTREMADAMENTE INFLAMABLE. DAÑOSO O FATAL SI SE INGIERE. VAPOR ES DAÑOSO. USE SOLO CON VENTILACIÓN ADECUADA. CONTENIDO BAJO PRESIÓN – SI SE CALIENTA PUEDE EXPLOTAR. PUEDE CAUSAR IRRITACIÓN EN LOS OJOS, PIEL Y TRACTO RESPIRATORIO.

MANTÉNGASE FUERA DEL ALCANCE DE LOS NIÑOS

Coverage: up to 600 Lineal feet of grout per can

Net Wt. 15 oz (425 g)

StoneDefender™ can be applied to grout 30 - 60 minutes after installing new or cleaning existing grout. It penetrates into grout or other porous surfaces and leaves no hard to remove residue..

Ver las instrucciones y precauciones en español en www.stoneandgroutproducts.com/label

DIRECTIONS:

**** Read entire label before using. ** Area to be sprayed should be well ventilated. Open windows and doors and use fans to circulate air.**

FOR PROFESSIONAL USE: Test product in an inconspicuous area to determine suitability for intended use. Surface to be sprayed must be clean and free from wax, sealants, or coatings. Holding the tip of the can 12-16 inches from the surface to be sealed, point the spray tip of the can at the surface and press the spray tip to apply. Apply product evenly. Wipe off excess sealer from glazed tile using a soft cotton or microfiber cloth .

Allow sealer to cure for 24 hours. For extra porous surfaces, a second coat may be needed. Sealer will dry to the touch in approximately one hour at 75°F.

NOTE: Surfaces which are not to be sealed should be protected with masking material.

MAINTENANCE: Clean treated areas with water and a non-acidic cleaner.

EXPECTED WEAR: Up to 10 years depending on the type of surface, usage, and proper maintenance. This is not a warranty.

WARRANTY: Instructions on this label are a guide and should not be considered complete. In the event of failure, the only obligation shall be to replace such product proven defective. Neither seller nor manufacturer shall be liable for any injury or inability to use this product. It is the user's responsibility to ascertain the suitability, safety and toxicity of this product and assumes all liability and risk therefor.

Clear Coat Max. MIR < 0.85

This product complies with the California Air Resources Board regulations
WARNING: This product may contain chemicals known by the State of California to cause cancer and birth defects or other reproductive harm.

The contents of this aerosol are CFC free.

The manufacturer of this product is dedicated to preserving the environment.

**** PRECAUTIONS:** Contains aliphatic hydrocarbons (8052-41-3), Acetone (67-64-1), Parachlorobenzotrifluoride (98-56-6), Hydrocarbon Propellant (68476-86-8), N-Butyl Acetate (123-86-4), Proprietary polymer.

HMS

Health hazards 2
Physical hazards 0

Flammability 3
Personal Protection C

HMS

Riesgos para la salud 2
Peligros físicos 0

Inflamabilidad 3
Protección personal C

Distributed by SPC Products, LLC

623-680-8275 – Info@groutdf.com

IN CASE OF EMERGENCY CALL INFOTRAC AT: 800-535-5053

DANGER

Extremely Flammable Aerosol
Extremely Flammable Gas
Highly Flammable Liquid and Vapor



Harmful if swallowed

Causes serious eye irritation

May cause genetic defects

May cause cancer

May cause drowsiness or dizziness

Causes damage to organs through prolonged or repeated exposure

Harmful to aquatic life with long lasting effects

May be fatal if swallowed and enters airways

Pressurized Container: may burst if heated

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Use personal protective equipment as required.

Wash face, hands and any exposed skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Do not breathe dust/fume/gas/mist/vapors/spray.

Avoid release to the environment.

Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

Pressurized container: Do not pierce or burn, even after use.

Do not spray on an open flame or other ignition source.

Keep container tightly closed. Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools. Take precautionary measures against static discharge.

Keep cool.

Store locked up.

Store in a well-ventilated place. Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/122 °F.

Dispose of contents/container to an approved waste disposal plant.

FIRST AID

IF EXPOSED OR CONCERNED: Get medical advice/attention. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

IF ON SKIN (or Hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Rinse mouth. **IF SWALLOWED:** Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

In case of fire: Use water to extinguish. In case of fire: Use CO2, dry chemical, or foam for extinction.